

# tesa® 60733

# **Product Information**



# tesa® 60733 100 µm thermal management tape

# **Product Description**

tesa® 60733 is a transfer type of thermal management tape which is designed for high thermal conductivity with mounting on heat source components in electronics devices.

#### **Product Features**

- · Excellent surface wet-out
- High thermal conductivity in z-direction
- · Strong bonding strength
- · Excellent electrical insulation

# **Application Fields**

- · Lamination on heat source components for cooling down
- Vapor chamber or heat pipe lamination
- · Antenna mounting for heat transfer

# Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

•	Backing	none	•	Total thickness	100 μm
•	Type of adhesive	acrylic	•	Color	white
•	Type of liner	PET film	•	Color of liner	transparent

# **Properties/Performance Values**

Thermal conductivity z-direction 0.7 W/mK
Wetting 92 %

### Adhesion to Values

• Steel (initial) 5 N/cm



# tesa® 60733

**Product Information** 

### **Additional Information**

Thermal conductivity measured by ASTM D5470

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

