


## Solutions for Fixation, Protection, and Light Blocking


## **Key features**

- · Light blocking in xy- and z-direction
- · High temperature resistant with PI film
- Matte black with low gloss level
- Solvent resistance
- Ultra-thin design of 5  $\mu m$  and 10  $\mu m$
- · Anti-Fingerprint

## **Typical applications**

- Graphite sheet, magnetic sheet protection
- FPC, PCB covering
- · Display light blocking







## Covering tapes – Assortment overview

		Single-sided PET	Single-sided Polyimide
		tesa® 79xx	tesa® 673xx
Product group description		**	
10.000		<ul><li>Repulsion resistant adhesive</li><li>Very good light-blocking with black backing and adhesive</li></ul>	<ul> <li>Repulsion resistant adhesive</li> <li>High temperature resistance and flame resistant properties achievable with PI film</li> </ul>
Thickness in µm		Black	Black
	5	7905 <b>(NEW)</b>	
	10	7910	67310
	20	7920	67320
	30	7930	67330
	50	7950	67350

Notes.	

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical

experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Notes.